

# THERM DEVELOPER PM / A

# DEVELOPER FOR THERMAL CTP PLATES READY-TO-USE AND MONOCOMPONENT

## **CHARACTERISTICS:**

Excellent developing results. It contains aluminium protectors. It maintains tanks and filters of plates Processor extremely clean, reducing cleaning operations, due to encrustations. High stability. It is recommended for use with plates processors with dipped brushes.

#### **APPLICATION:**

The product is ready-to-use and it can be used both as developer and as replenisher. We suggest anyhow to replace the bath at least once a month. The product is suitable to following plates, with relevant working temperatures:

	Brand and type of plates	Working Temp.	Contact time	Replenishm. ml/mq	Antiox. ml/hr
THERMAL PLATES	AGFA ENERGY ELITE PRO	22 ° C (± 1°)	25-28"	100-120	120-140
	KODAK CAPRICORN VT	23 ° C (± 1°)	25-35"	100-120	120-140
	KODAK ELECTRA XD	23 ° C (± 1°)	25-30"	100-120	120-140
	KODAK SWORD	23 ° C (± 1°)	25-35"	100-120	120-140
	FUJI BRILLIA LH-PCE	24 ° C (± 1°)	30-35"	100-120	120-140
	HUAGUANG TP U	23 ° C (± 1°)	25-35"	100-120	120-140
	CTP PLATE TP-S8	23 ° C (± 1°)	25-35"	100-120	120-140
	IPAGSA UNIVERSE 02	23 ° C (± 1°)	25-35"	100-120	120-140

Physical state:	Colour:	Odour :	II. > 12
LIQUID	ORANGE	ODOURLESS	pH: > <b>13</b>
Conductivity at 25°C:	Boiling Point :	Flash Point :	Water solubility:
83 – 87 mS	>100°C	NOT FLAMMABLE	COMPLETE

### **PRECAUTIONS:** Before using THERM DEVELOPER PM / A, read carefully its Safety Data

**Sheet**. We suggest to clean the Plate Processor with SOLVINE CTP and to rinse carefully, to eliminate incrustations which could come off using product.

Storage temperature : +5 / +25°C

**PACKING:** 20 liters plastic cans

200 liters drums

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee. Specifications subject to change without notice.





Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Em ail: info@imaf.it - internet: www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643