

ACTIVAL

High viscosity cleaner to prepare and clean offset plates

Detergent and antioxidant emulsion for positive and negative offset plates.

High solvent power on ink. Its abrasive characteristic makes it effective to oxide removal, due to not perfect plates filing

Working instructions

- Shake well before use.
- Apply ACTIVAL directly on plates surface, using a wet sponge, with pressure sufficient to removal of ink or of eventual oxide.
- Wash off with water or with wetting solution.

Precautions

- Being the cleaner slightly abrasive, please do not exert too much pressure during use on NOT BAKED analogue and digital, CTP and CtCP plates.
- Do not leave it in printing areas for long time without rinsing it

Main characteristics

- Suitable for all kind of Offset plates: analogue and digital, CTP and CtCP positive and negative ones.
- High solvent power for a quick ink removal
- Abrasive characteristic for oxidation and scratches removal.
- It improves the ink acceptance in printing areas and water acceptance in not printing areas.
- Easy use.

Physical characteristics

Appearance	Pink emulsion
Density	1,040 Kg/lt
рН 25°C	1,00
Flash Point	63°C
Volatile Organic Compound (VOC)	35%
Ink removal	high

Safety

Read the safety specifications before using this product

Packing

Carton 6 cans x 2 litres

Storage

- Store at room temperature, in dry and well aired place
- Keep far from heat and direct sunlight.
- Keep closed the containers.
- Storage time: 12 months from the production date.

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee.

Specifications subject to change without notice.



Industria Materiali Fotochimici Via Galvani, 2 - 20068 Peschiera Borromeo (MI S.p.A. Em ail: info@imaf.it - internet: www.imaf.it Tel. ++39 0255302615 - ++39 0255302643