

TP 3001

SPECIFIC SOLUTION FOR PLATES BAKING TREATMENT

Working Instructions

Plates Processor application:

- Fill up the Plates Processor.
- Regenerate regularly to maintain the correct level.
- In case of problems, check density that must correspond to starting value.

Manual application:

- Apply a thin and uniform layer on the whole plate surface.
- Well spread with dry cloth
- Let it dry before introducing the plate in the oven.

Precautions

We recommend to remove always the product with water after baking treatment, TP 3001 is not suitable for archiving.

Main characteristics:

- TP 3001 is a water ready-to-use solution, to protect plates during baking treatment
- Studied for use in Plates Processors and manual application
- It can be used in all types of plates processors
- It prevents background fog
- Suitable to all plates,
- Short time storage before baking

Physical characteristics:

Appearance	Colourless liquid
Density	1,030 Kg/lt
рН 25°С	5.00
Flash point	Not flammable

Storage

- Store at room temperature, in dry and well-aired place
- Keep far from heat and direct sunlight.
- Keep closed the containers.
- Storage time: 12 months from production date.

Safety

Read safety specifications before using this product.

Packing

10 litres cans

The information given in this sheet is to be considered reliable and is provided in good faith but without guarantee. Subject to change without notice

