



NEOGUM

Synthetic finishing gum for offset plates

Finisher gum for use in Plates Processor, with high protection characteristics against oxidation. It contains the latest developed preserving substances and pH stabilizers to prevent bad smell.

SUITABLE TO USE WITH CTP (THERMAL 830 AND VIOLET) AND CTCP PLATES

Working instructions

MACHINE APPLICATION :

- Fill up plates processor with diluted product 1 : 1 and place it in gumming section.
- Replenish regularly, always with diluted product 1: 1, to keep the right level.
- If problems occur, please check density that must always keep the starting value.
- **For long storage use pure product, not diluted**

Precautions for use in Plates processor

- Take care of dryer temperature that has always to be included between 40°C and 50°C.

Main characteristics

- Ready –to-use (dilutable up to 1:1)
- Studied for application in machine
- Easy to use.
- It prevents oxide formation.
- It prevents algae and mould formations.
- Suitable to all offset plates.
- It can be used in all types of plates processors .
- Excellent protection properties.

Physical properties of concentr. product

| | |
|--------------------|-----------------------|
| Appearance | Amber coloured liquid |
| Density | 1,070 Kg/lt |
| pH at 25°C | 6,50 |
| Flash point | Not flammable |

Safety

Read Safety Specifications before using this product

Packing

10 litres cans

Storage

- Store at room temperature, in dry and well-aired place
- Keep far from heat and direct sunlight.
- Keep closed the containers.
- Storage time : 12 months from production date

The information given in this sheet is to be considered reliable and is provided in good faith but without guarantee. Specifications subject to change without notice.



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Email: info@imaf.it - internet : www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643