



DRY INK FOUNT ECO

Drying agent for dampening waters

Working instructions

To be added directly to already mixed dampening solution, in quantity depending on acceleration degree of requested drying and on support type.
Suggested dose : 1 - 3%.

Precautions

Always handle with care and keep to the safety advice mentioned on the label.
After printing, wash the machine

Main characteristics

- Rapid printing surface drying
- Rub resistance of ink is improved
- Fewer hardened ink residues on rubber blankets
- It facilitates more rapid processing of print stacks
- Especially suited for non-or poorly absorbing substrates
- Compatible with all concentrated fountain solutions

Physical characteristics

Appearance	liquid
Density	1,087 Kg/lit
pH 25°C	4.37-4.77
Colour	red
Flash Point	Not flammable
Water solubility	Fully soluble

Safety

Read the safety specifications before using this product

Packing

Carton 6 cans x 1 lt

Storage

- Store at room temperature, in dry and well aired place
- Keep far from heat and direct sunlight.
- Keep closed the containers.
- Storage time : 12 months from the production date.

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee.
Specifications subject to change without notice.



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Em ail: info@imaf.it - internet : www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643