



# ROTO-START

## Anti-tearing and anti-dryer product for offset inks

### Working instructions

#### Manual Use :

- Use a hand-spray, keeping a distance of 20-30 cm.
- Spray it uniformly on interested area.

### Main characteristics:

- Low volatility, soft smell product
- Free from aromatic and chlorinated compounds.
- It does not damage rubbers, nor it attacks plates coating.
- Product is used as anti-tearing diluent for traditional offset inks.
- Suitable to all kinds of inks.
- Compatible with most offset plates

### Safety

Read Safety specifications before using this product

### Packing

6 x 1 litre, by vaporizer  
10 litres cans  
200 litres drums

### Storage

- Store at room temperature, in dry and well-aired place
- Keep far from heat and direct sunlight.
- Keep closed the container
- Storage time : 24 months from production date

### Waste

If possible collect and send them to an authorized waste management firm, in compliance with local and national regulations.

### Properties

Chemical characteristics	Appearance	Light yellow liquid
	Odour	Characteristic
	Flash Point	> 61°C
	Density (25°C)	0,794 Kg/lt
	Solubility	Not water soluble

Too long contact on plates or too excessive wipe can damage the image.

The information given in this sheet is to be considered reliable and is provided in good faith but without guarantee.  
Subject to change without notice.

V. 2 - 10/2013 MB



**imaf** S.p.A.

Industria Materiali Fotochimici  
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)  
Email: info@imaf.it - internet : www.imaf.it  
Tel. ++39 0255302615 - ++39 0255302643