



SCHIUMA STOP

Anti- foam for offset printing

Working instructions

Hand use:

- Suggested dosage is included between 10 cc and 20 cc of anti-foam for each liter of damping solution (tank).
- Mix well

Main characteristics

- Anti-foam product developed expressly for damping solutions, with which it is compatible both for chemical and functional characteristics.
- Absolutely necessary whenever there are unexpected foams in damping recycling systems.

Safety

Read Safety Data Sheet before using this product.

Packing

Carton containing Nr 6 bottles / 1 lt

Storage

- Store at room temperature, in dry and well aired place
- Keep far from heat and direct sunlight
- Maintain closed the containers
- Storage time : 24 months from production date

Waste

If possible collect and send them to an authorized waste management firm, in compliance with local and national regulations.

Properties

Chemical characteristics	Appearance	Colourless liquid
	Odour	Typical
	Boiling Point	82°C
	Flash point	12°C
	Water Solubility	Water soluble

Too long contact time on plates or too excessive wipe can damage the image

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee.
Specifications subject to change without notice.



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
E-mail: info@imaf.it - internet : www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643