



# ANILOX CLEAN

## PRODUCT TO REMOVE WATER BASED VARNISHES AND INKS

### Working instructions for hand use

- **Flexo : cleaning of anilox rollers**  
**Coating unit of acrylic varnishes**  
 Pour product on a cloth or sponge and spread it on concerned areas.  
 Remove product with water, better warm one.
- **Varnishing circuits**  
 We recommend the dilution from 1 to 3, up to a maximum of 1 to 10, according to the degree of dirt. Pour the diluted product into the circuit and let it act for 5/10 min.  
 The diluted product can be used for several washes : recover it and rinse with water.

### Main point

- Too long contact on plate or too excessive wipe can damage the image

### Main characteristics

- Specific concentrated product to remove water based varnishes from small cells of anilox cylinders.
- Suitable to clean blankets and polymer varnishing plates
- Very active product
- Quick in removing
- It allows an immediate start up in printing or filing.
- Not flammable product.

### Safety

Read Safety Data Sheet before using this product

### Packing

10 lt / can

### Storage

- Store at room temperature, in dry and well-aired place
- Keep far from heat and direct sunlight.
- Keep closed the container
- Storage time : 12 months from production date

### Physical Properties

<b>Chemical characteristics</b>	<b>Appearance</b>	Green liquid
	<b>Odour</b>	Typical
	<b>Boiling Point</b>	140°C
	<b>Flash Point</b>	Not determ.
	<b>Water Solubility</b>	yes

Information given in this sheet is to be considered reliable and is provided in good faith but without guarantee.  
 Subject to change without notice.