



# CERAMIC CLEANER

**SPECIAL PRODUCT for CLEANING OF CERAMIC AND CHROMIUM-PLATED SCREENED CYLINDERS**

**HIGHLY ACTIVE, FOR USE BOTH IN AND OUT OF MACHINE**

## Working Instructions

- Always shake well before use.

### In machine

- Apply uniformly, making ceramic and chromium-plated screened cylinders turn.
- Let it act from 10 minutes up to some hours
- Rinse well with water (preferably warm one, 40°C), eventually using installation circuit.

### Out of machine

- Dose on cylinder a plentiful layer of product by brush and, eventually, cover with an extensible plastic sheet (so that product does not drip).
- Let it act for several hours
- Rinse well with powerful water stream.
- If the cylinder is much obstructed, repeat the operation.

We recommend to repeat at least weekly .

## Precautions

- Avoid long contacts with aluminium.

## Main characteristics

- Quick and thorough cleaning
- Suitable to all kinds of inks and varnishes
- Easy use

## Physical properties

Appearance	black liquid
Density	1,070 Kg/lt
pH 25°C	12,00
Flash point	100°C
Organic Volatile Compounds (VOC)	0%
Ink or varnish removal	High

## Safety

Read the safety specifications before using this product

## Packing

Carton of 4 bottles x 0,5 litres

## Storage

- Store at room temperature, in dry and well-aired place
- Keep far from heat and direct sunlight.
- Keep closed the containers.
- Storage time : 12 months from production date.

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee. Specifications subject to change without notice.



**imaf** S.p.A.

Industria Materiali Fotochimici  
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)  
Email: info@imaf.it - internet : www.imaf.it  
Tel. ++39 0255302615 - ++39 0255302643