



FLEXO SP-28

CONCENTRATED DETERGENT TO CLEAN FLEXOGRAPHIC PRINTING DEPT.

Working Instructions

MANUAL USE

- For general use, dilute FLEXO SP-28 up to 10% in water (1 liter product in 10 liters water)
- FLEXO SP-28 can be applied by sponge or brush or vaporized.
- Let it act for some minutes, then remove residues of dirt by a cloth, rinse and dry.

USE IN PARTS WASHING TRAYS

- For use in parts washing machine, dilute FLEXO SP-28 up to 50% in water (5 liters of product in 10 liters of water)
- Use it according to procedure of parts washing machine

Precautions

- **do not use in contact with alkali sensitive materials**

Main characteristics

- Particularly indicated to remove inks residues and encrustations from rollers, frame works and equipment.
- Thanks to its high emulsifying power, it quickly and efficaciously removes accumulations and fat dirty residues, also from floors and washable surfaces
- Also suitable to uses with warm water on high pressure spray machines.

Physical properties

Appearance	Amber coloured liquid
Density	1,158 Kg/lit
pH 25°C	>13
Flash point	/

Safety

Read the safety specifications before using this product

Packing

PE 20 lt can

Storage

- Store at room temperature, in dry and well-aired place
- Keep far from heat and direct sunlight.
- Keep closed the containers.
- Storage time : 12 months from production date.

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee.
Specifications subject to change without notice.



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Email: info@imaf.it - internet : www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643