



THERM REPLENISHER PM-R

REPLENISHER OF THERM DEVELOPER PM/A

CHARACTERISTICS: Concentrated replenisher, it allows to reduce replenishment rates, keeping unaltered bath characteristics.

APPLICATION : Product is ready-to-use and it has to be used as replenisher. We suggest anyhow to replace the bath at least once a month. The product is suitable to following plates, with relevant working temperatures:

	Brand and type of plates	Replishm. ml/sqm	Antiox. ml/hr
<u>THERMAL PLATES</u>	AGFA ENERGY ELITE PRO	80-120	100
	KODAK CAPRICORN VT	80-120	100
	KODAK ELECTRA XD	80-120	100
	TWS DIAMOND TH	80-120	100
	FUJI BRILLIA LH-PCE	80-120	100
	HUAGUANG TP U	80-120	100
	ABEZETA INFINITY	80-120	100
	IPAGSA UNIVERSE 02	80-120	100

Physical state : LIQUID	Colour: COLOURLESS	Odour: ODOURLESS	pH: > 13
Conductiv. at 25°C: 89 – 92 mS	Boiling point : > 100°C	Flash Point : NON FLAMMABLE	Water Solubility: COMPLETE

PRECAUTIONS: Before using THERM REPLENISHER PM-R the first time, read carefully its Safety Data Sheet. We suggest to clean the Plate Processor with SOLVINE CTP and to rinse carefully, to eliminate incrustations which could come off using product. Storage temperature : + 5 / +25°C Use product ONLY with THERM DEVELOPER PM A

PACKING: 20 liters plastic cans
200 liters drums

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee. Specifications subject to change without notice.

- Storage time : 18 months after production date



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Email: info@imaf.it - internet : www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643