



Technical Data Sheet

THERM REPLENISHER PM-R

PLUS « LOW CHEM »

REPLENISHER

REPLENISHER OF THERM DEVELOPER PM/A

CHARACTERISTICS:

Extremely concentrated replenisher, it allows to reduce replenishment rates, keeping unaltered bath characteristics.

APPLICATION :

Product is ready-to-use and it has to be used as replenisher.
We suggest anyhow to replace the bath at least once a month.

Product is suitable to following plates, with relevant working temperatures:

	Brand and type of plates	Replenishm. ml/sqm	Antiox. ml/hr
<u>THERMAL PLATES</u>	AGFA ENERGY ELITE PRO	50-70	70
	KODAK CAPRICORN VT	50-70	70
	KODAK ELECTRA XD	50-70	70
	TWS DIAMOND TH	50-70	70
	FUJI BRILLIA LH-PCE	50-70	70
	ABEZETA INFINITY	50-70	70
	HUAGUANG TP U	50-70	70
	IPAGSA UNIVERSE 02	50-70	70

Physical state : LIQUID	Colour: COLOURLESS	Odour: ODOURLESS	pH: > 13
Conductivity at 25°C: 96 – 99 mS	Boiling point : > 100°C	Flash Point : NON FLAMMABLE	Water Solubility: COMPLETE

PRECAUTIONS: Before using the product, read carefully its Safety Data Sheet. We suggest to clean the Plate Processor with SOLVINE CTP and to rinse carefully, to eliminate incrustations which could come off using product.

PACKING :

20 liters plastic cans/200liters drums

Storage time : 18 months after production date

Information given in this sheet is considered to be reliable and is provided in good faith but without guarantee.
Specifications subject to change without notice.



imaf S.p.A.

Industria Materiali Fotochimici
Via Galvani, 2 - 20068 Peschiera Borromeo (MI)
Email: info@imaf.it - internet : www.imaf.it
Tel. ++39 0255302615 - ++39 0255302643